

STAINLESS STEEL DOOR UNDERBAR FRIDGE

SS=STAINLESS STEEL, GD = GLASS

MODEL	DESCRIPTION Plain Top Underbar	WEIGHT (kg)	DIMENSIONS (L X B X H) mm	POWER Watts
UFPTSD-1180-1.5	1.5 SS Doors with one height adjustable shelf per full door	80	1180x650x900	375
UFPTSD-1780-2.5	2.5 SS Doors with one height adjustable shelf per full door	110	1780x650x900	450
UFPTSD-2380-3.5	3.5 SS Doors with one height adjustable shelf per full door	125	2380x650x900	450
UFPTSD-3000-4.5	4.5 SS Doors with one height adjustable shelf per full door	140	3000x650x900	615

MODEL	DESCRIPTION 100mm Splash Back to rear Under Bar	WEIGHT (kg)	DIMENSIONS (L X B X H) mm	POWER Watts
UFSBSD-1180-1.5	1.5 SS Doors with one height adjustable shelf per full door	83	1180x650x900	375
UFSBSD-1780-2.5	2.5 SS Doors with one height adjustable shelf per full door	115	1780x650x900	450
UFSBSD-2380-3.5	3.5 SS Doors with one height adjustable shelf per full door	131	2380x650x900	450
UFSBSD-3000-4.5	3.5 SS Doors with one height adjustable shelf per full door	147	3000x650x900	615

- Self-contained forced-air condensing unit utilising ozone friendly R134A refrigerant with auto evaporating pan.
- Economical and easily replaceable disposable filters on the condenser radiator.
- Digital display controller with splashguard and condenser filter service indicator.
- Angled louvres to deflect the hot air away from the doors.
- Doors: Self-closing with magnetic clip on door gaskets.
- Host of optional extras available - please enquire.





GLASS DOOR UNDERBAR FRIDGE

SS=STAINLESS STEEL, GD = GLASS

MODEL	DESCRIPTION Plain Top Underbar	WEIGHT (kg)	DIMENSIONS (L X B X H) mm	POWER Watts
UFPTGD-1180-1.5	1.5 GD Doors with one height adjustable shelf per full door and light.	85	1180x650x900	375
UFPTGD-1780-2.5	2.5 GD Doors with one height adjustable shelf per full door and light.	120	1780x650x900	450
UFPTGD-2380-3.5	3.5 GD Doors with one height adjustable shelf per full door and light.	140	2380x650x900	450
UFPTGD-3000-4.5	4.5 GD Doors with one height adjustable shelf per full door and light.	160	3000x650x900	615



MODEL	DESCRIPTION (100mm Splash Back to rear Under Bar)	WEIGHT (kg)	DIMENSIONS (L X B X H) mm	POWER Watts
UFSBGD-1180-1.5	1.5 GD Doors with one height adjustable shelf per full door and light.	88	1180x650x900	375
UFSBGD-1780-2.5	2.5 GD Doors with one height adjustable shelf per full door and light.	125	1780x650x900	450
UFSBGD-2380-3.5	3.5 GD Doors with one height adjustable shelf per full door and light.	146	2380x650x900	450
UFSBGD-3000-4.5	4.5 GD Doors with one height adjustable shelf per full door and light.	167	3000x650x900	615

- Self-contained forced-air condensing unit utilising ozone friendly R134A refrigerant with auto evaporating pan.
- Economical and easily replaceable disposable filters on the condenser radiator.
- Digital display controller with splashguard and condenser filter service indicator.
- Angled louvres to deflect the hot air away from the doors.
- Doors: Self-closing with magnetic clip on door gaskets.
- Comes with energy saving LED light
- Host of optional extras available- please enquire.

STAINLESS STEEL DOOR GASTRONORM UNDERBAR FRIDGE

SS=STAINLESS STEEL, GD = GLASS

MODEL	DESCRIPTION	WEIGHT (kg)	DIMENSIONS (L X B X H) mm	POWER Watts
	Plain Top Underbar			
UFPTSD-1350-2.5GN	2.5 SS Doors with one GN1/1 variable racking systems per full door	92	1350x650x900	375
UFPTSD-1780-3.5GN	3.5 SS Doors with one GN1/1 variable racking systems per full door	128	1780x650x900	450
UFPTSD-2380-4.5GN	4.5 SS Doors with one GN1/1 variable racking systems per full door	149	2380x650x900	450
UFPTSD-3000-5.5GN	5.5 SS Doors with one GN1/1 variable racking systems per full door	170	3000x650x900	615

MODEL	DESCRIPTION	WEIGHT (kg)	DIMENSIONS (L X B X H) mm	POWER Watts
	100mm Splash Back to rear Under Bar			
UFSBSD-1350-2.5GN	2.5 SS Doors with one GN1/1 variable racking systems per full door	95	1350x650x900	375
UFSBSD-1780-3.5GN	3.5 SS Doors with one GN1/1 variable racking systems per full door	133	1780x650x900	450
UFSBSD-2380-4.5GN	4.5 SS Doors with one GN1/1 variable racking systems per full door	155	2380x650x900	450
UFSBSD-3000-5.5GN	5.5 SS Doors with one GN1/1 variable racking systems per full door	177	3000x650x900	615



GLASS DOOR GASTRONORM UNDERBAR FRIDGE

SS=STAINLESS STEEL, GD = GLASS

MODEL	DESCRIPTION	WEIGHT (kg)	DIMENSIONS (L X B X H) mm	POWER Watts
	Plain Top Underbar			
UFPTGD-1350-2.5GN	2.5 GD Doors with one GN1/1 variable racking systems per full door and light.	102	1350x650x900	375
UFPTGD-1780-3.5GN	3.5 GD Doors with one GN1/1 variable racking systems per full door and light.	143	1780x650x900	450
UFPTGD-2380-4.5GN	4.5 GD Doors with one GN1/1 variable racking systems per full door and light.	169	2380x650x900	450
UFPTGD-3000-5.5GN	5.5 GD Doors with one GN1/1 variable racking systems per full door and light.	195	3000x650x900	615

MODEL	DESCRIPTION	WEIGHT (kg)	DIMENSIONS (L X B X H) mm	POWER Watts
	100mm Splash Back to rear Under Bar			
UFSBGD-1350-2.5GN	2.5 GD Doors with one GN1/1 variable racking systems per full door and light.	105	1350x650x900	375
UFSBGD-1780-3.5GN	3.5 GD Doors with one GN1/1 variable racking systems per full door and light.	148	1780x650x900	450
UFSBGD-2380-4.5GN	4.5 GD Doors with one GN1/1 variable racking systems per full door and light.	175	2380x650x900	450
UFSBGD-3000-5.5GN	5.5 GD Doors with one GN1/1 variable racking systems per full door and light.	204	3000x650x900	615

- Self-contained forced-air condensing unit utilising ozone friendly R134A refrigerant with auto evaporating pan.
- Economical and easily replaceable disposable filters on the condenser radiator.
- Digital display controller with splashguard and condenser filter service indicator.
- Angled louvres to deflect the hot air away from the doors.
- Doors: Self-closing with magnetic clip on door gaskets.
- Host of optional extras available - please enquire.



RAISED PIZZA TOP TO REAR UNDERBAR FRIDGE

SS=STAINLESS STEEL, GD = GLASS

MODEL	DESCRIPTION Plain Top Under Bar	WEIGHT (kg)	DIMENSIONS (L X B X H) mm	POWER Watts
UFSTSD-1180-1.5	1.5 SS Doors with one height adjustable shelf -6 inserts 1/6	86	1180 x 650 x 900	375
UFSTSD-1780-2.5	2.5 SS Doors with two height adjustable shelves-10 inserts 1/6	119	1780 x 650 x 900	450
UFSTSD-2380-3.5	3.5 SS Doors with three height adjustable shelves-13 inserts 1/6	137	2380 x 650 x 900	450
UFSTSD-3000-4.5	4.5 SS Doors with four height adjustable shelves-17 inserts 1/6	155	3000 x 650 x 900	615

MODEL	DESCRIPTION Plain Top Under Bar	WEIGHT (kg)	DIMENSIONS (L X B X H) mm	POWER Watts
UFPBGD-1180-1.5	1.5 GD Doors with one height adjustable shelf -6 inserts 1/6	91	1180 x 650 x 900	375
UFPBGD-1780-2.5	2.5 GD Doors with two height adjustable shelves-10 inserts 1/6	129	1780 x 650 x 900	450
UFPBGD-2380-3.5	3.5 GD Doors with three height adjustable shelves-13 inserts 1/6	152	2380 x 650 x 900	450
UFPBGD-3000-4.5	4.5 GD Doors with four height adjustable shelves-17 inserts 1/6	175	3000 x 650 x 900	615

- Self-contained forced-air condensing unit utilising ozone friendly R134A refrigerant with auto evaporating pan.
- Economical and easily replaceable disposable filters on the condenser radiator.
- Digital display controller with splashguard and condenser filter service indicator.
- Angled louvres to deflect the hot air away from the doors.
- Doors: Self-closing with magnetic clip on door gaskets.
- Pizza top is insulated and includes a night cover, inserts are excluded.
- Host of optional extras available - please enquire.



POLAR TOP UNDERBAR

SS=STAINLESS STEEL, GD = GLASS

MODEL	DESCRIPTION Plain Top Under Bar	WEIGHT (kg)	DIMENSIONS (L X B X H) mm	POWER Watts
UFPPTSD-1180-1.5	1.5 SS Doors with one height adjustable shelf -polar top 100mm	88	1180 x 650 x 900	375
UFPPTSD-1780-2.5	2.5 SS Doors with two height adjustable shelf -polar top 100mm	125	1780 x 650 x 900	450
UFPPTSD-2380-3.5	3.5 SS Doors with three height adjustable shelf -polar top 100mm	146	2380 x 650 x 900	450
UFPPTSD-3000-4.5	4.5 SS Doors with four height adjustable shelf -polar top 100mm	167	3000 x 650 x 900	615

- Self-contained forced-air condensing unit utilising ozone friendly R134A refrigerant with auto evaporating pan.
- Economical and easily replaceable disposable filters on the condenser radiator.
- Digital display controller with splashguard and condenser filter service indicator.
- Angled louvres to deflect the hot air away from the doors.
- Doors: Self-closing with magnetic clip on door gaskets.
- Host of optional extras available- please enquire.

SLIDE TOP UNDERBAR

SS=STAINLESS STEEL, GD = GLASS

MODEL	DESCRIPTION	WEIGHT	DIMENSIONS	POWER
	Plain Top Underbar	(kg)	(L X B X H) mm	Watts
UFSTSD-1180-1.0	1 bottom loading SS Door with 1 fixed shelf & 2 sliding lids	83	1180 x 650 x 900	375
UFSTSD-1780-2.0	2 bottom loading SS Doors with 2 fixed shelves & 3 sliding lids	115	1780 x 650 x 900	450
UFSTSD-2380-3.0	3 bottom loading SS Doors with 3 fixed shelves & 4 sliding lids	131	2380 x 650 x 900	450
UFSTSD-3000-4.0	4 bottom loading SS Doors with 4 fixed shelves & 5 sliding lids	147	3000 x 650 x 900	615

- Self-contained forced-air condensing unit utilising ozone friendly R134A refrigerant with auto evaporating pan.
- Economical and easily replaceable disposable filters on the condenser radiator.
- Digital display controller with splashguard and condenser filter service indicator.
- Angled louvres to deflect the hot air away from the doors.
- Loading Doors: Self-closing with magnetic clip on door gaskets.
- Host of optional extras available- please enquire.



UNDERBAR HAMPERS FRIDGE

SS=STAINLESS STEEL, GD = GLASS

MODEL	DESCRIPTION	WEIGHT	DIMENSIONS	POWER
	Plain Top Underbar	(kg)	(L X B X H) mm	Watts
UFHAMSD-1180-1.5	1.5 SS Doors with one height adjustable shelf per full door	80	1180x650x900	375
UFHAMSD-1780-2.5	2.5 SS Doors with one height adjustable shelf per full door	110	1780x650x900	450
UFHAMSD-2380-3.5	3.5 SS Doors with one height adjustable shelf per full door	125	2380x650x900	450
UFHAMSD-3000-4.5	4.5 SS Doors with one height adjustable shelf per full door	140	3000x650x900	615

MODEL	DESCRIPTION	WEIGHT	DIMENSIONS	POWER
	Plain Top Underbar	(kg)	(L X B X H) mm	Watts
UFHAMGD-1180-1.5	1.5 GD Doors with one height adjustable shelf per full door and light.	85	1180x650x900	375
UFHAMGD-1780-2.5	2.5 GD Doors with one height adjustable shelf per full door and light.	120	1780x650x900	450
UFHAMGD-2380-3.5	3.5 GD Doors with one height adjustable shelf per full door and light.	140	2380x650x900	450
UFHAMGD-3000-4.5	4.5 GD Doors with one height adjustable shelf per full door and light.	160	3000x650x900	615



- Self-contained forced-air condensing unit utilising ozone friendly R134A refrigerant with auto evaporating pan.
- Economical and easily replaceable disposable filters on the condenser radiator.
- Digital display controller with splashguard and condenser filter service indicator.
- Angled louvres to deflect the hot air away from the doors.
- Loading Doors: Self-closing with magnetic clip on door gaskets.
- 200mm x 20mm thick food grade Polyethylene cutting board across the front length of the top and cut-outs at the rear for GN inserts specified by the client.
- Host of optional extras available - please enquire.

ICE BIN

MODEL	DESCRIPTION	WEIGHT	DIMENSIONS	STORAGE CAPACITY
	Ice Bin	(kg)	(L X B X H) mm	(kg)
UFSTSD-1180-1.0	Ice Bin - 274 kg (Stainless Steel)	60	1000x750x1000	274
UFSTSD-1780-2.0	Ice Bin - 342 kg (Stainless Steel)	75	1250x750x1000	342

- Door for easy access to ice.
- Magnet door gaskets.
- 430 Stainless Steel, double skinned construction.
- Drain pipe welded in.

